

# GPCZ.EX2102 - Dry-chemical Extinguishers, Portable, Marine

## Dry-chemical Extinguishers, Portable, Marine

See General Information for Dry-chemical Extinguishers, Portable, Marine

### BADGER FIRE PROTECTION

1016 Corporate Park Dr  
Mebane, NC 27302-8368 USA

EX2102

### Cartridge-activated-type Extinguishers

Model	Nominal Agent Capacity lb	Min Use Temp, °F	Rating	Marine Classification	
				Type A Size	Type B:C Size
<b>Ammonium phosphate</b>					
B-10-A	10.65	-40	4-A:40-B:C	II	II
B-10-A-HF	10.65	-40	1-A:20-B:C	II	II
B-20-A	21	-40	10-A:60-B:C	II	III
B-20-A-HF	21	-40	2-A:40-B:C	II	III
B-30-A	25	-40	10-A:80-B:C	II	III
B-30-A-HF	25	-40	3-A:40-B:C	II	III
<b>Potassium Bicarbonate</b>					
B-10-PK	10.5	-40	60-B:C	—	II
B-10-PK-HF	10.5	-40	20-B:C	—	II
B-20-PK	22	-40	80-B:C	—	III
B-20-PK-HF	22	-40	20-B:C	—	III
B-20-PKW-HF	22	-40	20-B:C	—	III
B-30-PK	28.5	-40	120-B:C	—	III
B-30-PK-HF	28.5	-40	40-B:C	—	III
B-30-PKW-HF	28.5	-40	40-B:C	—	III
<b>Sodium Bicarbonate</b>					
B-10-RG	12	-40	40-B:C	—	II
B-20-RG	23	-40	60-B:C	—	III

B-30-RG	29	-40	120-B:C	—	III
---------	----	-----	---------	---	-----

## Stored-pressure-type Extinguishers

Model	Nominal Agent Capacity lb	Min Use Temp, °F	Rating	Marine Classification	
				Type A Size	Type B:C Size
<b>Ammonium phosphate</b>					
PRO PLUS 2.5 MP, PRO PLUS 2.5 MP-1, B250M, 250 MB-1, 250 MB-2, ADV-250	2.5	-40	1-A:10-B:C	—	I
ADV-4, ADV-4-1	4	-40	2-A:10-B:C	—	I
5MB-8H	5	-40	2-A:40-B:C	II	I
PRO PLUS 5 MP, 5MB-6H, 5MB-7H, B5M, ADV-550	5	-40	3-A:40-B:C	II	I
B10M-1-HF	10	-40	1-A:20-B:C	II	II
ADV-10	10	-40	4-A:60-B:C	II	II
PRO PLUS 10 MP, B10M-1, B10M, 10MB-8H	10	-40	4-A:80-B:C	II	II
B20M-HF	20	-40	4-A:60-B:C	II	III
ADV-20	20	-40	6-A:80-B:C	II	III
PRO PLUS 20 MP, B20M, 20MB-6H	20	-40	6-A:120-B:C	II	III
50MB	50	-40	20-A:160-B:C	II	V
<b>Potassium Bicarbonate</b>					
250PB-2, B250P	2.5	-40	10-B:C	—	I
5PB-5	5	-40	10-B:C	—	I
5PB-4H, B5P	5	-40	30-B:C	—	I
B10P-1-HF	10	-40	20-B:C	—	II
10PB-6H, B10P, (PRO 10 PKM-3)	10.25	-40	80-B:C	—	II
B20P-HF	20	-40	60-B:C	—	III
20PB-3H, B20P	20.5	-40	120-B:C	—	III
50PB	50	-40	160-B:C	—	V

<b>Sodium Bicarbonate</b>					
B275BC	2.75	-40	10-B:C	—	I
B5BC	5.5	-40	40-B:C	—	I
B10BC	10.25	-40	60-B:C	—	II
10RB-7H	10.5	-40	60-B:C	—	II
20RB-7H, B20BC	20.5	-40	120-B:C	—	III
50RB	50	-40	160-B:C	—	V

Last Updated on 2014-04-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"